


Verbindungstechnik




Zylinderstifte		DIN 6325 / ISO 8734			
Typ Stahl gehärtet & geschliffen	D	mögliche Länge L	L1	L2	R
6325-2 x **	2	6 - 8 - 10 - 12 - 14 - 16 - 18 - 20	0,78	0,30	2
6325-3 x **	3	8 - 10 - 12 - 14 - 16 - 18 - 20 - 22 - 24 - 28 - 30 - 32	1,10	0,45	3
6325-4 x **	4	8 - 10 - 12 - 14 - 16 - 18 - 20 - 22 - 24 - 28 - 30 - 32 - 36 - 40	1,40	0,60	4
6325-5 x **	5	10 - 12 - 14 - 16 - 18 - 20 - 22 - 24 - 28 - 30 - 32 - 36 - 40 - 45 - 50	1,70	0,75	5
6325-6 x **	6	10 - 12 - 14 - 16 - 18 - 20 - 22 - 24 - 28 - 30 - 32 - 36 - 40 - 45 - 50 - 60	2,10	0,90	6
6325-8 x **	8	12 - 14 - 16 - 18 - 20 - 22 - 24 - 28 - 30 - 32 - 36 - 40 - 45 - 50 - 55 - 60 - 70 - 80	2,60	1,20	8
6325-10 x **	10	16 - 20 - 24 - 28 - 30 - 32 - 36 - 40 - 45 - 50 - 55 - 60 - 70 - 80 - 90 - 100	3,00	1,50	10
6325-12 x **	12	20 - 24 - 28 - 32 - 36 - 40 - 45 - 50 - 55 - 60 - 70 - 80 - 90 - 100 - 120	3,80	1,80	12
6325-14 x **	14	28 - 36 - 40 - 45 - 50 - 60 - 70 - 80 - 90 - 100 - 120	3,80	2,00	16
6325-16 x **	16	40 - 45 - 50 - 55 - 60 - 70 - 80 - 90 - 100 - 120	4,70	2,50	16

** bitte gewünschte Länge eintragen

☞ Bestellbeispiel: 6325-2x**

Standardtyp

gewünschte Länge L:	
6 mm	14 mm
8 mm	16 mm
10 mm	18 mm
12 mm	20 mm



Zylinderstifte mit Innengewinde		DIN 7979 D / ISO 8735 A					
Typ Stahl gehärtet & geschliffen	D	mögliche Länge L	G	L1	L2	L3	R
7979-5 x **	5	16 - 20 - 24 - 28 - 32 - 36 - 40	M 3	1,7	0,6	6	5
7979-6 x **	6	16 - 18 - 20 - 24 - 28 - 32 - 36 - 40 - 45 - 50 - 55 - 60	M 4	2,1	0,8	6	6
7979-8 x **	8	20 - 24 - 28 - 32 - 36 - 40 - 45 - 50 - 55 - 60 - 70 - 80	M 5	2,6	1,0	8	8
7979-10 x **	10	20 - 24 - 28 - 32 - 36 - 40 - 45 - 50 - 55 - 60 - 70 - 80 - 90 - 100	M 6	3,0	1,2	10	10
7979-12 x **	12	32 - 36 - 40 - 45 - 50 - 55 - 60 - 70 - 80 - 90 - 100 - 120	M 6	3,8	1,6	12	12
7979-14 x **	14	36 - 40 - 50 - 60 - 70 - 80 - 100	M 8	4,0	1,8	12	14
7979-16 x **	16	40 - 45 - 50 - 55 - 60 - 70 - 80 - 90 - 100 - 120	M 8	4,7	2,0	16	16
7979-20 x **	20	45 - 50 - 60 - 70 - 80 - 90 - 100 - 120	M 10	6,0	2,5	20	20

** bitte gewünschte Länge eintragen

☞ Bestellbeispiel: 7979-5x**

Standardtyp

gewünschte Länge L:	
16 mm	32 mm
20 mm	36 mm
24 mm	40 mm
28 mm	