


parallel gripper HGPD-20-A-G2

Part number: 1132941

FESTO

With gripping force backup when closing...-G2.



Data sheet

Feature	Value
Size	20
Stroke per gripper jaw	4 mm
Max. replacement accuracy	≤ 0.2 mm
Max. angular gripper jaw backlash ax,ay	≤ 0.1 deg
Max. gripper jaw backlash Sz	≤ 0.02 mm
Rotationally symmetrical	≤ 0.2 mm
Repetition accuracy, gripper	≤ 0.04 mm
Number of gripper fingers	2
Assembly position	Any
Mode of operation	double-acting
Gripper function	Parallel
Gripper force back-up	On closing
Design structure	Inclined plane guided motion sequence
Position detection	For proximity sensor
Operating pressure	4 ... 8 bar
Operating pressure, sealing air	0 ... 0.5 bar
Max. operating frequency of gripper	≤ 3 Hz
Min. opening time at 6 bar	35 ms
Min. closing time at 6 bar	18 ms
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Protection class	IP65
Ambient temperature	5 ... 60 °C
Mass moment of inertia	0.52 kgcm ²
Max. torque at gripper Mx static	12 Nm
Max. torque at gripper My static	7 Nm
Max. torque at gripper Mz static	6 Nm
Lubrication interval for guide components	5,000,000 Mio SP
Max. mass per external gripper finger	57 g
Product weight	182 g
Mounting type	Internal thread and centring sleeve With through-hole and centring sleeve With through-hole and dowel pin With internal thread and dowel pin Optional
Pneumatic connection, sealing air	M3
Pneumatic connection	M5
Materials note	Free of copper and PTFE Conforms to RoHS
Material cover cap	High alloy steel, non-corrosive
Material housing	Aluminium Anodised
Material gripper jaws	Steel Hardened