
## semi-rotary drive DSM-T-40-270-FW-A-B Part number: 1145132







## **Data sheet**

| Feature                                 | Value  |
|---|--|
| Size                                    | 40   |
| Swivel angle                            | 0 270 deg  |
| Assembly position                       | Any  |
| Mode of operation                       | double-acting  |
| Design structure                        | Rotary vane  |
| Position detection                      | For proximity sensor                                     |
| Operating pressure                      | 2 10 bar   |
| Max. swivel frequency at 6 bar          | 2 Hz   |
| Operating medium                        | Compressed air in accordance with ISO8573-1:2010 [7:-:-] |
| Corrosion resistance classification CRC | 0 - No corrosion stress                                  |
| Ambient temperature                     | -10 60 °C  |
| Max. axial force                        | 120 N  |
| Max. radial force                       | 350 N  |
| Theoretical torque at 6 bar             | 40 Nm  |
| Product weight                          | 3,705 g  |
| Mounting type                           | with internal (female) thread                            |
| Pneumatic connection                    | G1/8   |
| Materials note                          | Free of copper and PTFE                                  |
|   | Conforms to RoHS   |
| Material of drive shaft                 | Steel  |
|   | Nickel plated  |
| Material seals                          | TPE-U(PU)  |
| Material housing                        | Wrought Aluminium alloy                                  |