


# fitting NPCK-C-D-G14-K10

Part number: 1489336

FESTO



## Data sheet

| Feature                                       | Value   |
|---|---|
| Size  | Standard  |
| Nominal size                                  | 6.1 mm  |
| Type of seal on screw-in stud                 | Sealing ring  |
| Assembly position                             | Any   |
| Container size                                | 1   |
| Operating pressure complete temperature range | -0.95 ... 12 bar  |
| Operating medium                              | Compressed air in accordance with ISO8573-1:2010 [7:-:-]<br>Water as per manufacturer's declaration at <a href="http://www.festo.com">www.festo.com</a> |
| Note on operating and pilot medium            | Lubricated operation possible   |
| Corrosion resistance classification CRC       | 4 - Very high corrosion stress  |
| Food-safe                                     | See Supplementary material information  |
| Ambient temperature                           | -20 ... 120 °C  |
| Nominal tightening torque                     | 20 Nm   |
| Tolerance for nominal tightening torque       | ± 10 %  |
| Product weight                                | 32.9 g  |
| Pneumatic connection, port 1                  | Male thread G1/4  |
| Pneumatic connection, port 2                  | For tubing outside diameter 10 mm   |
| Material of threaded plug                     | High alloy steel, non-corrosive   |
| Materials note                                | Conforms to RoHS  |
| Material sealing ring                         | PEEK  |
| Material housing                              | High alloy steel, non-corrosive   |