



one-way flow control valve GRLA-1/8-RS-B

Part number: 151169

FESTO

With knurled screw and lock nut



Data sheet

| Feature | Value |
|--|---|
| Valve function | One-way flow control function for exhaust air |
| Pneumatic connection, port 1 | G1/8 |
| Pneumatic connection, port 2 | G1/8 |
| Adjusting element | Knurled screw |
| Mounting type | Threaded |
| Standard nominal flow rate in flow control direction | 340 l/min |
| Standard nominal flow rate in non-return direction | 260 ... 420 l/min |
| Ambient temperature | -10 ... 60 °C |
| Maritime classification | see certificate |
| Assembly position | Any |
| Operating pressure complete temperature range | 0.3 ... 10 bar |
| Standard flow rate in direction of flow control: 6 → 0 bar | 615 l/min |
| Standard flow rate in blocked direction: 6 → 0 bar | 470 ... 760 l/min |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Medium temperature | -10 ... 60 °C |
| Max. tightening torque | 6 Nm |
| Product weight | 30 g |
| Material of threaded plug | Wrought Aluminium alloy |
| Materials note | Conforms to RoHS |
| Material seals | NBR |
| Material adjusting screw | Brass |
| Material swivel fitting | Zinc die-casting |