



# solenoid valve

## JMFH-5/2-D-1-S-C

Part number: 152563

FESTO

With manual overrides, without solenoid coils or sockets. Solenoid coils and sockets should be ordered separately.



## Data sheet

| Feature                               | Value  |
|---------------------------------------|--|
| Valve function                        | 5/2 bistable   |
| Type of actuation                     | electrical   |
| Width                                 | 42 mm  |
| Standard nominal flow rate            | 1,200 l/min  |
| Operating pressure                    | -0.9 ... 16 bar  |
| Design structure                      | Piston slide   |
| Maritime classification               | see certificate  |
| Protection class                      | IP65   |
| Nominal size                          | 8 mm   |
| Grid dimension                        | 43 mm  |
| Exhaust-air function                  | throttleable   |
| Sealing principle                     | soft   |
| Assembly position                     | Any  |
| Conforms to standard                  | ISO 5599-1   |
| Manual override                       | with accessories, detenting<br>Pushing   |
| ISO code                              | 169  |
| Type of piloting                      | Piloted  |
| Pilot air supply                      | external   |
| Flow direction                        | reversible   |
| Overlap                               | Positive overlap   |
| Pilot pressure                        | 2 ... 10 bar   |
| Switching time reversal               | 16 ms  |
| Max. positive test pulse with logic 0 | 2,200 µs   |
| Max. negative test pulse with logic 1 | 3,700 µs   |
| Operating medium                      | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                                       |
| Note on operating and pilot medium    | Lubricated operation possible (subsequently required for further operation)                    |
| Vibration resistance                  | Transport application test at severity level 1 in accordance with FN 942017-4 and EN 60068-2-6 |
| Shock resistance                      | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27              |
| Medium temperature                    | -10 ... 60 °C  |
| Sound pressure level                  | 85 dB(A)   |
| Pilot medium                          | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                                       |
| Ambient temperature                   | -5 ... 40 °C   |
| Product weight                        | 490 g  |
| Electrical connection                 | Via F coil, must be ordered separately   |
| Mounting type                         | On sub-base<br>with through hole   |
| Pilot air port 12                     | Connection plate size 1 as per ISO 5599-1  |
| Pilot air port 14                     | Connection plate size 1 as per ISO 5599-1  |
| Pneumatic connection, port 1          | Connection plate size 1 as per ISO 5599-1  |

| Feature                      | Value                                     |
|------------------------------|---|
| Pneumatic connection, port 2 | Connection plate size 1 as per ISO 5599-1 |
| Pneumatic connection, port 3 | Connection plate size 1 as per ISO 5599-1 |
| Pneumatic connection, port 4 | Connection plate size 1 as per ISO 5599-1 |
| Pneumatic connection, port 5 | Connection plate size 1 as per ISO 5599-1 |
| Materials note               | Conforms to RoHS                          |
| Material seals               | HNBR<br>NBR                               |
| Material housing             | Aluminium die cast                        |