


# compact cylinder AEVUZ-16-25-P-A

Part number: 157215  
Classic - do not use for new projects

FESTO

For proximity sensing, piston-rod end with female thread.  
Modern alternatives can be found by entering the first four characters of the type code in the search field.



## Data sheet

| Feature                                    | Value   |
|--|---|
| Stroke                                     | 25 mm   |
| Piston diameter                            | 16 mm   |
| Cushioning                                 | P: Flexible cushioning rings/plates at both ends                            |
| Assembly position                          | Any   |
| Mode of operation                          | single-acting<br>pulling action   |
| Piston-rod end                             | Female thread   |
| Design structure                           | Piston<br>Piston rod  |
| Position detection                         | For proximity sensor  |
| Variants                                   | Single-ended piston rod   |
| Operating pressure                         | 1.3 ... 10 bar  |
| Operating medium                           | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                    |
| Note on operating and pilot medium         | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC    | 2 - Moderate corrosion stress   |
| Ambient temperature                        | -20 ... 80 °C   |
| Impact energy in end positions             | 0.1 J   |
| Theoretical force at 6 bar, advance stroke | 81 N  |
| Moving mass with 0 mm stroke               | 12 g  |
| Additional weight per 10 mm stroke         | 15 g  |
| Basic weight for 0 mm stroke               | 89 g  |
| Additional mass factor per 10 mm of stroke | 4 g   |
| Mounting type                              | with through hole<br>with accessories<br>Optional                           |
| Pneumatic connection                       | M5  |
| Material of flange screw                   | High alloy steel, non-corrosive   |
| Material cover                             | Wrought Aluminium alloy   |
| Material of dynamic seals                  | NBR<br>TPE-U(PU)  |
| Material piston rod                        | High alloy steel, non-corrosive   |
| Material cylinder barrel                   | Wrought Aluminium alloy   |