



# twin-piston cylinder

## DPZ-20-10-P-A-KF-S2

Part number: 162068

FESTO

With two parallel piston rods, for proximity sensing, with elastic cushioning rings in end positions.



## Data sheet

| Feature                                    | Value   |
|--|---|
| Stroke                                     | 10 mm   |
| Adjustable end-position range/length       | 10 mm   |
| Piston diameter                            | 20 mm   |
| Operating mode of drive unit               | Yoke  |
| Cushioning                                 | P: Flexible cushioning rings/plates at both ends                            |
| Assembly position                          | Any   |
| Guide                                      | Recirculating ball bearing guide  |
| Design structure                           | Guide   |
| Position detection                         | For proximity sensor  |
| Variants                                   | Through piston rod  |
| Operating pressure                         | 1 ... 10 bar  |
| Mode of operation                          | double-acting   |
| Operating medium                           | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                    |
| Note on operating and pilot medium         | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC    | 0 - No corrosion stress   |
| Ambient temperature                        | -20 ... 80 °C   |
| Impact energy in end positions             | 0.2 Nm  |
| Theoretical force at 6 bar, return stroke  | 282 N   |
| Theoretical force at 6 bar, advance stroke | 282 N   |
| alternative connections                    | See product drawing   |
| Pneumatic connection                       | M5  |
| Material cover                             | Wrought Aluminium alloy   |
| Material seals                             | NBR   |
| Material housing                           | Wrought Aluminium alloy   |
| Material piston rod                        | Case-hardened steel   |