
## vacuum generator VADMI-200-P Part number: 162532 Classic - do not use for new projects

With additional vacuum switch, PNP design Modern alternatives can be found by entering the first four characters of the type code in the search field.





**FESTO** 

## **Data sheet**

| Feature                                       | Value  |
|---|--|
| Nominal size, Laval nozzle                    | 2 mm   |
| Grid dimension                                | 22 mm  |
| Design, silencer                              | closed   |
| Assembly position                             | Any  |
| Ejector characteristic                        | High vacuum  |
| Grade of filtration                           | <= 40 μm   |
| Manual override                               | Pushing  |
| Integrated function                           | Ejector pulse valve, electrical                          |
|   | Flow control valve                                       |
|   | Electrical on-off valve                                  |
|   | Filter   |
|   | Non-return valve   |
|   | Vacuum switch  |
| Measured variable                             | Relative pressure  |
| Measuring principle                           | Piezoresistive   |
| Switching element function                    | Normally open contact                                    |
| Switching function                            | Threshold value comparator                               |
| Valve function                                | closed   |
| Polarity protected                            | for all electrical connections                           |
| Type of display                               | LED  |
| Hysteresis adjustment range [bar]             | -0.50.05 bar   |
| Setting options                               | Potentiometer  |
| Operating status display                      | Optical  |
| Threshold setting range                       | -0.9 0 bar   |
| Operating pressure                            | 2 8 bar  |
| Max. vacuum                                   | 85 %   |
| Nominal operating pressure                    | 6 bar  |
| Overload range                                | 5 bar  |
| Air supply time at nominal operating pressure | 0.15 s   |
| Operating voltage range DC                    | 21.6 26.4 V  |
| Duty cycle                                    | 100 %  |
| Switch output                                 | PNP  |
| Authorisation                                 | RCM Mark   |
|   | c UL us - Recognized (OL)                                |
| CE mark (see declaration of conformity)       | to EU directive for EMC                                  |
| Operating medium                              | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium            | Lubricated operation not possible                        |
| Corrosion resistance classification CRC       | 2 - Moderate corrosion stress                            |
| Medium temperature                            | 0 60 °C  |
| Protection class                              | IP65   |
| Ambient temperature                           | 0 50 °C  |
| Product weight                                | 360 g  |



| Feature                      | Value                         |
|------------------------------|-------------------------------|
| Pressure measuring range     | 0 1 bar                       |
| Electrical connection        | 4-pin                         |
|                              | M8x1                          |
|                              | Plug                          |
| Mounting type                | with through hole             |
|                              | with internal (female) thread |
|                              | Optional                      |
| Pneumatic connection, port 1 | G1/4                          |
| Pneumatic connection, port 3 | Integrated silencer           |
| Vacuum connection            | G3/8                          |
| Materials note               | Free of copper and PTFE       |
|                              | Conforms to RoHS              |
| Material seals               | NBR                           |
| Material receiver nozzle     | Nickel-plated brass           |
| Material filter              | PA                            |
| Material filter housing      | PC                            |
| Material housing             | Wrought Aluminium alloy       |
| Material silencer            | PE                            |
|                              | POM                           |
| Material piston              | POM                           |
| Material transmitter nozzle  | Nickel-plated brass           |