
fine filter combination LFMBA-1/4-D-MINI Part number: 162659 Classic - do not use for new projects

Micro filter 1 μm for prefiltration and micro filter 0.01 $\mu m,$ with metal bowl guard.

Modern alternatives can be found by entering the first four characters of the type code in the search field.



Data sheet

Feature	Value
Size	Mini
Series	D
Assembly position	Vertical +/- 5°
Grade of filtration	0.01 µm
Filter efficiency	99.9999 %
Condensate drain	manual rotary
Design structure	Fibre filter
Max. condensate volume	22 ml
Bowl guard	Metal bowl guard
Operating pressure	1 16 bar
Operating medium	Compressed air in accordance with ISO8573-1:2010 [6:8:4]
	Inert gases
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [1:7:2]
	Inert gases
Medium temperature	1.5 60 °C
Residual oil content	0.01 mg/m3
Ambient temperature	-10 60 °C
Product weight	500 g
Mounting type	Line installation
	with accessories
Pneumatic connection, port 1	G1/4
Pneumatic connection, port 2	G1/4
Materials note	Free of copper and PTFE
	Conforms to RoHS
Material filter	Boron silicate fibre
Material housing	Zinc die-casting
Material bowl	PC



