

## fine filter combination LFMBA-3/8-D-MINI Part number: 162660 Classic - do not use for new projects

Micro filter 1  $\mu m$  for prefiltration and micro filter 0.01  $\mu m,$  with metal bowl guard.

Modern alternatives can be found by entering the first four characters of the type code in the search field.





**FESTO** 

## **Data sheet**

Feature	Value
Size	Mini
Series	D
Assembly position	Vertical +/- 5°
Grade of filtration	0.01 μm
Filter efficiency	99.9999 %
Condensate drain	manual rotary
Design structure	Fibre filter
Max. condensate volume	22 ml
Bowl guard	Metal bowl guard
Operating pressure	1 16 bar
Operating medium	Compressed air in accordance with ISO8573-1:2010 [6:8:4]
	Inert gases
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [1:7:2]
	Inert gases
Medium temperature	1.5 60 °C
Residual oil content	0.01 mg/m3
Ambient temperature	-10 60 °C
Product weight	500 g
Mounting type	Line installation
	with accessories
Pneumatic connection, port 1	G3/8
Pneumatic connection, port 2	G3/8
Materials note	Free of copper and PTFE
	Conforms to RoHS
Material filter	Boron silicate fibre
Material housing	Zinc die-casting
Material bowl	PC