
service unit LFR-1/2-D-MAXI-KE-A Part number: 186048 Classic - do not use for new projects

consisting of filter regulator and distributor module, without socket, with mounting brackets.

With automatic condensate drain.

Modern alternatives can be found by entering the first four characters of the type code in the search field.





FESTO

Data sheet

Feature	Value
Size	Maxi
Series	D
Actuator lock	Rotary knob with lock
Assembly position	Vertical +/- 5°
Grade of filtration	40 μm
Condensate drain	fully automatic
Design structure	Branching module
	Pressure sensor
	Filter regulator with pressure gauge
Max. condensate volume	80 cm3
Bowl guard	Metal bowl guard
Pressure gauge	with pressure gauge
Operating pressure	2 12 bar
Pressure regulation range	0.5 12 bar
Max. pressure hysteresis	0.2 bar
Standard nominal flow rate	9,200 l/min
Maritime classification	see certificate
Operating medium	Compressed air in accordance with ISO8573-1:2010 [-:-:-]
	Inert gases
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [7:8:4]
	Inert gases
Medium temperature	-10 60 °C
Ambient temperature	-10 60 °C
Product weight	2,400 g
Mounting type	Line installation
	with accessories
	Optional
Pneumatic connection, port 1	G1/2
Pneumatic connection, port 2	G1/2
Material housing	Zinc die-casting
Material bowl	PC