
suction cup ESS-8-SS Part number: 189281

E55-8-55
Part number: 189281

Wearing part, easily replaceable





Data sheet

| Feature | Value |
|-----------------------------------------------|--------------------------------------------------|
| Min. workpiece radius | 20 mm |
| Nominal size | 2 mm |
| suction cup diameter | 8 mm |
| suction cup volume | 0.03 cm3 |
| Ejector pulse suitability | <= 4 bar |
| Position of connection | on top |
| Assembly position | Any |
| Correlation to suction-cup holder | Size 2 |
| Suction cup shape | round flat |
| Operating pressure | 0 0.95 bar |
| Nominal operating pressure | -0.7 bar |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7:-:-] |
| Corrosion resistance classification CRC | 1 - Low corrosion stress |
| Food-safe | See Supplementary material information |
| Ambient temperature | -30 180 °C |
| Retention force at nominal operating pressure | 2.3 N |
| Lateral force at nominal operating pressure | 3.5 N |
| Product weight | 0.2 g |
| Mounting type | Via vacuum port |
| Vacuum connection | Inside diameter 4 mm |
| Colour | transparent |
| Shore hardness | 50 +/- 5 |
| Material of threaded plug | Nickel-plated brass |
| Materials note | Free of copper and PTFE |
| | Contains PWIS substances |
| | Conforms to RoHS |
| Material suction cup | VMQ (silicon) |