suction cup ESS-150-SU Part number: 189327

easily interchangeable,

FESTO





Data sheet

| Feature | Value |
|---|--|
| Min. workpiece radius | 480 mm |
| Nominal size | 10 mm |
| suction cup diameter | 150 mm |
| suction cup volume | 173.826 cm3 |
| Position of connection | on top |
| Assembly position | Any |
| Correlation to suction-cup holder | Size 6 |
| Suction cup shape | round flat |
| Operating pressure | 0 0.95 bar |
| Nominal operating pressure | -0.7 bar |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7:-:-] |
| Corrosion resistance classification CRC | 1 - Low corrosion stress |
| Food-safe | See Supplementary material information |
| Ambient temperature | -20 60 °C |
| Retention force at nominal operating pressure | 900 N |
| Lateral force at nominal operating pressure | 1,000 N |
| Product weight | 719 g |
| Mounting type | Via vacuum port |
| Vacuum connection | M20x2 |
| Colour | blue |
| Shore hardness | 60 +/- 5 |
| Material of threaded plug | NBR |
| | Steel, nickel-plated |
| | Galvanised and chrome-plated steel |
| Materials note | Free of copper and PTFE |
| | Contains PWIS substances |
| | Conforms to RoHS |
| Material suction cup | PUR |