
suction cup ESS-15-EU Part number: 189335

easily interchangeable,



Data sheet

Feature	Value
Min. workpiece radius	20 mm
Nominal size	2 mm
suction cup diameter	15 mm
suction cup volume	0.35 cm3
Position of connection	on top
Assembly position	Any
Correlation to suction-cup holder	Size 3
Suction cup shape	Round, extra deep
Operating pressure	0 0.95 bar
Nominal operating pressure	-0.7 bar
Operating medium	Atmospheric air based on ISO 8573-1:2010 [7:-:-]
Corrosion resistance classification CRC	1 - Low corrosion stress
Food-safe	See Supplementary material information
Ambient temperature	-20 60 °C
Retention force at nominal operating pressure	9.8 N
Lateral force at nominal operating pressure	15 N
Product weight	1.9 g
Mounting type	Via vacuum port
Vacuum connection	M4
Colour	blue
Shore hardness	60 +/- 5
Material of threaded plug	Nickel-plated brass
Operating pressure Nominal operating pressure Operating medium Corrosion resistance classification CRC Food-safe Ambient temperature Retention force at nominal operating pressure Lateral force at nominal operating pressure Product weight Mounting type Vacuum connection Colour Shore hardness	Free of copper and PTFE
	Contains PWIS substances
	Conforms to RoHS
Material suction cup	PUR

FESTO

