
suction cup ESS-20-EN Part number: 189338

easily interchangeable,



Data sheet

| Feature | Value |
|---|--|
| Min. workpiece radius | 30 mm |
| Nominal size | 3 mm |
| suction cup diameter | 20 mm |
| suction cup volume | 0.84 cm3 |
| Position of connection | on top |
| Assembly position | Any |
| Correlation to suction-cup holder | Size 4 |
| Suction cup shape | Round, extra deep |
| Operating pressure | 0 0.95 bar |
| Nominal operating pressure | -0.7 bar |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7:-:-] |
| Corrosion resistance classification CRC | 1 - Low corrosion stress |
| Food-safe | See Supplementary material information |
| Ambient temperature | -10 70 °C |
| Retention force at nominal operating pressure | 17 N |
| Lateral force at nominal operating pressure | 14 N |
| Product weight | 6.4 g |
| Mounting type | Via vacuum port |
| Vacuum connection | M6 |
| Colour | Black |
| Shore hardness | 60 +/- 5 |
| Material of threaded plug | Nickel-plated brass |
| | Galvanised and chrome-plated steel |
| Materials note | Free of copper and PTFE |
| | Conforms to RoHS |
| Material suction cup | NBR |

FESTO

