

service unit FRC-3/4-D-DI-MAXI-KB-A Part number: 192484 Classic - do not use for new projects

consisting of filter regulator, distributor module with pressure switch but without socket, and lubricator with mounting brackets. With automatic condensate drain and metal bowl guard.

Modern alternatives can be found by entering the first four characters of the type code in the search field.

Type to be discontinued. Available until 2022. See Support Portal for alternative products.





FESTO

Data sheet

Feature	Value
Size	Maxi
Series	D
Actuator lock	Rotary knob with lock
Assembly position	Vertical +/- 5°
Grade of filtration	40 μm
Condensate drain	fully automatic
Design structure	Branching module
	Pressure sensor
	Filter regulator with pressure gauge
	proportional standard mist lubricator
Max. condensate volume	43 cm3
Bowl guard	Metal bowl guard
Pressure gauge	with pressure gauge
Operating pressure	2 12 bar
Pressure regulation range	0.5 12 bar
Standard nominal flow rate	7,000 l/min
Maritime classification	see certificate
Operating medium	Compressed air in accordance with ISO8573-1:2010 [-:-:-]
	Inert gases
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [7:4:-]
	Inert gases
Medium temperature	-10 60 °C
Ambient temperature	-10 60 °C
Product weight	3,700 g
Mounting type	Line installation
	with accessories
	Optional
Pneumatic connection, port 1	G3/4
Pneumatic connection, port 2	G3/4
Material housing	Zinc die-casting
Material bowl	PC