
service unit FRCS-3/4-D-7-MAXI-A Part number: 194954 Classic - do not use for new projects

Filter/pressure regulator/lubricator combination, D series, with lockable regulator head.

Modern alternatives can be found by entering the first four characters of the type code in the search field.

Type to be discontinued. Available until 2022. See Support Portal for alternative products.





FESTO

Data sheet

Feature	Value
Size	Maxi
Series	D
Actuator lock	Rotary knob with integrated lock
Assembly position	Vertical +/- 5°
Condensate drain	fully automatic
Design structure	Filter regulator with pressure gauge
	proportional standard mist lubricator
Max. condensate volume	80 cm3
Grade of filtration	40 μm
Bowl guard	Metal bowl guard
Pressure gauge	with pressure gauge
Operating pressure	2 12 bar
Pressure regulation range	0.5 7 bar
Max. pressure hysteresis	0.4 bar
Standard nominal flow rate	8,500 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [-:-:-]
Medium temperature	-10 60 °C
Ambient temperature	-10 60 °C
Product weight	2,490 g
Mounting type	Line installation
	with accessories
Pneumatic connection, port 1	G3/4
Pneumatic connection, port 2	G3/4
Material housing	Zinc die-casting
Material bowl	PC