


bus module CPX-E-PN

Part number: 4080497

FESTO



Data sheet

Feature	Value
Dimensions W x L x H	42,2 mm x 125,8 mm x 76,5 mm
Grid dimension	18.9 mm
Diagnostics via LED	Force mode Network errors Network status port 1 Network status port 2 Power supply electronics/sensors Power supply load System error Maintenance required
Diagnostics via bus	Wire break Short circuit PROFIsafe addresses different parameterisation error Upper limit value not observed Overtemperature Lower limit value not observed Undervoltage
Configuration support	GSDML file
Max. no. of modules	10
System parameters	Diagnostic memory Fail-safe reaction Force mode System start
Module parameters	Channel alarms bundling Undervoltage diagnostics Channel alarms undervoltage Process value representation of analogue modules
Intrinsic current consumption at nominal operating voltage for electronics/sensors	Typically 75 mA
Max. power supply	8 A
Nominal operating voltage DC for electronics/sensors	24 V
Power failure buffering	20 ms
Permissible voltage fluctuations for electronics/sensors	± 25 %
Power supply, function	Electronics and sensors
Power supply, type of connection	Terminal strip
Power supply, connection technology	Cage clamp terminal
Power supply, number of pins/wires	4
Power supply, conductor diameter	0.2 ... 1.5 mm ²
Power supply, note on conductor diameter	0.2 - 2.5 mm ² for flexible conductors without wire end sleeves
Authorisation	RCM Mark
CE mark (see declaration of conformity)	to EU directive for EMC
Vibration resistance	Transport application test at severity level 1 in accordance with FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with severity level 1 in accordance with FN 942017-5 and EN 60068-2-27

Feature	Value
Corrosion resistance classification CRC	0 - No corrosion stress
Storage temperature	-20 ... 70 °C
Relative air humidity	95 % non-condensing
Protection against direct and indirect contact	Protective extra-low voltage with safe disconnection (PELV)
Protection class	IP20
Ambient temperature	-5 ... 50 °C
Note on ambient temperature	-5 - 60°C for vertical installation
Product weight	145 g
Maximum address volume for outputs	64 Byte
Note on outputs	62 bytes with I/O diagnostic interface 64 bytes with status bits 64 bytes without diagnostics
Maximum address volume for inputs	64 Byte
Note on inlets	62 bytes with I/O diagnostic interface 62 bytes with status bits 64 bytes without diagnostics
Fieldbus interface, electrical isolation	Yes
Fieldbus interface, transmission rate	100 Mbit/s
Fieldbus interface	Ethernet
Fieldbus interface, type of connection	2x socket
Fieldbus interface, connection technology	RJ45
Fieldbus interface, number of pins/wires	8
Fieldbus interface, protocol	PROFINET IRT PROFINET RT
Fieldbus interface, max. address volume for inputs	64 Byte
Fieldbus interface, max. address volume for outputs	64 Byte
Mounting type	with top-hat rail
Materials note	Contains PWIS substances Conforms to RoHS
Material housing	PA