


connecting cable

NEBM-L5G18-E-10-N-LE18

Part number: 4977494

FESTO



Data sheet

Feature	Value
Cable identification	Without inscription label holder
Electrical connection 1, function	Field device side
Electrical connection 1, design	Angular
Electrical connection 1, connection type	Plug socket
Electrical connection 1, cable outlet	Straight
Electrical connection 1, connection technology	Pin allocation L5
Electrical connection 1, number of pins/wires	18
Electrical connection 1, occupied pins/wires	18
Electrical connection 2, function	Controller side
Electrical connection 2, connection type	Cable
Electrical connection 2, connection technology	Open end
Electrical connection 2, number of pins/wires	18
Electrical connection 2, occupied pins/wires	18
Operating voltage range DC	0 ... 30 V
Operating voltage range AC	0 ... 30 V
Acceptable current load at 40°C	5 A
Surge strength	1.5 kV
Cable length	10 m
Cable attribute	Suitable for chain link trunking
Test conditions of cable	Test conditions on request
Bending radius, fixed cable installation	≥ 26 mm
Bending radius, flexible cable installation	≥ 43 mm
Cable diameter	8.5 mm
Cable structure	18x0,25
Nominal conductor cross-section	0.25 mm ²
Wire ends	Cut off bluntly
Protection class	IP20
Note on degree of protection	IP65 for mounting in terminal boxes
Ambient temperature	-40 ... 80 °C
Ambient temperature with flexible cable installation	-40 ... 80 °C
CE mark (see declaration of conformity)	in accordance with EU RoHS directive
Materials note	Conforms to RoHS
Degree of contamination	3
Corrosion resistance classification CRC	0 - No corrosion stress
Material cable sheath	TPE-U(PUR)
Cable sheath colour	Grey
Material housing	PA
Housing colour	Black
Material insulation	TPE-E