



# proximity sensor SIEF-M30NB-NS-K-L

Part number: 538322

FESTO

With cable, semi-flush mounting



## Data sheet

Feature	Value
Design	Round
Conforms to standard	EN 60947-5-2
Authorisation	RCM Mark c UL us - Listed (OL)
CE mark (see declaration of conformity)	to EU directive for EMC
Materials note	Free of copper and PTFE
Measuring principle	Inductive
Nominal switching distance	20 mm
Guaranteed switching distance	16.2 mm
Reduction factors	Aluminium = 1.0 Stainless steel, St 18/8 = 1.0 Copper = 1.0 Brass = 1.0 Steel, St 37 = 1.0
Ambient temperature	-30 ... 85 °C
Repetition accuracy	0.4 mm
Switch output	NPN
Switching element function	Normally open contact
Hysteresis	0.6 ... 3 mm
Max. switching frequency, DC	1,500 Hz
Max. output current	200 mA
Voltage drop	≤ 1.8 V
Short circuit strength	Pulsing
Operating voltage range DC	10 ... 30 V
Residual ripple	10 %
Idle current	≤ 15 mA
Polarity protected	for all electrical connections
Electrical connection	3-core Cable
Cable length	2.5 m
Material cable sheath	TPE-U(PUR)
Material insulation	PVC
Size	M30
Mounting type	with lock nut
Tightening torque	75 Nm
Type of installation	Semi-flush
Product weight	194 g
Material housing	Brass PBT Chromed-plated
Operating status display	Yellow LED
Ambient temperature with flexible cable installation	0 ... 80 °C
Protection class	IP67
Interference immunity to magnetic fields	DC and AC magnetic field
Corrosion resistance classification CRC	2 - Moderate corrosion stress