## filter regulator PCRP-64-N12-7-E-R1-M-T19 Part number: 5394675







## **Data sheet**

Feature	Value
Size	64
Series	Р
Actuator lock	Adjusting screw with lock
Assembly position	Vertical +/- 5°
Grade of filtration	40 μm
Condensate drain	manual rotary
Design structure	Filter regulator without pressure gauge
Conforms to standard	NACE MR0175/ISO 15156 (housing and bowl)
Max. condensate volume	30 cm3
Controller function	with initial pressure compensation
	with secondary exhaust
Pressure gauge	Prepared for G1/4
Operating pressure	1 20 bar
Pressure regulation range	0.5 7 bar
Max. pressure hysteresis	0.2 bar
Max. standard flow rate	6,750 l/min
Standard nominal flow rate	4,455 l/min
Operating medium	Compressed air to ISO 8573-1:2010 [-:4:-]
	Inert gases
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further
	operation)
Storage temperature	-60 80 °C
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Medium temperature	-60 80 °C
Ambient temperature	-60 80 °C
Product weight	1,910 g
Mounting type	Line installation
3 71	With mounting kit
	Optional
Pressure gauge connection	G1/4
Pneumatic connection, port 1	NPT1/2-14
Pneumatic connection, port 2	NPT1/2-14
Material of drain screw	High alloy steel, non-corrosive
Material number of drain screw	1.4404/316L
Material of filter holder	Stainless steel casting
Material number of filter support	1.4409/CF3M(316L)
Materials note	Contains PWIS substances
	Conforms to RoHS
Material mounting bracket	High alloy steel, non-corrosive
Material seals	CR
	NBR
	VMQ
	High alloy steel, non-corrosive
Material filter	High alloy steel, non-corrosive
Material number of filter	1.4404/316L
Material housing	Stainless steel casting
Material number for housing	1.4409/CF3M(316L)
Material adjusting screw	High alloy steel, non-corrosive
Material bowl	Stainless steel casting
Material number of bowl	1.4409/CF3M (316L)
material number of bowl	1.44UY/CF)NI (310L)