



# parallel gripper HGP-25-A-B-SSK

Part number: 539635

FESTO

self-centring, can be used as internal and external gripper, for position sensing, with protective dust cap.



## Data sheet

Feature	Value
Size	25
Stroke per gripper jaw	7.5 mm
Max. replacement accuracy	0.2 mm
Repetition accuracy, gripper	< 0.04 mm
Number of gripper fingers	2
Assembly position	Any
Gripper function	Parallel
Design structure	Lever
Position detection	For proximity sensor
Total force at 6 bar, opening	370 N
Total force at 6 bar, closing	340 N
Operating pressure	2 ... 8 bar
Max. operating frequency of gripper	4 Hz
Min. opening time at 6 bar	47 ms
Min. closing time at 6 bar	50 ms
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	1 - Low corrosion stress
Protection class	IP54
Ambient temperature	5 ... 60 °C
Gripping force per gripper jaw at 6 bar, opening	185 N
Gripping force per gripper jaw at 6 bar, closing	170 N
Mass moment of inertia	3.831 kgcm <sup>2</sup>
Max. force on gripper jaw Fz static	240 N
Max. torque at gripper Mx static	11 Nm
Max. torque at gripper My static	11 Nm
Max. torque at gripper Mz static	11 Nm
Max. mass per external gripper finger	80 g
Product weight	737 g
Mounting type	Internal thread and centring sleeve With through-hole and centring sleeve
Pneumatic connection	G1/8
Materials note	Free of copper and PTFE
Material cover cap	TPV
Material housing	Aluminium Hard anodised
Material gripper jaws	High alloy steel