


one-way flow control valve GRLSA-1/4-QS-8

Part number: 540662

FESTO



Data sheet

Feature	Value
Valve function	One-way flow control function for exhaust air
Pneumatic connection, port 1	QS-8
Pneumatic connection, port 2	G1/4
Type of actuation	manual
Adjusting element	Internal hex
Mounting type	Threaded
Standard nominal flow rate in flow control direction	0 ... 450 l/min
Standard nominal flow rate in non-return direction	390 ... 570 l/min
Ambient temperature	-10 ... 60 °C
Assembly position	Any
Operating pressure complete temperature range	0.2 ... 10 bar
Standard flow rate in direction of flow control: 6 -> 0 bar	0 ... 700 l/min
Standard flow rate in blocked direction: 6 -> 0 bar	820 ... 930 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Storage temperature	-10 ... 40 °C
Medium temperature	-10 ... 60 °C
Nominal tightening torque	11 Nm
Tolerance for nominal tightening torque	± 10 %
Product weight	34.8 g
Materials note	Free of copper and PTFE
Material seals	NBR
Material hollow bolt	Wrought Aluminium alloy Anodised
Material release ring	POM
Material adjusting screw	PA-reinforced
Material swivel fitting	Zinc die-casting