

## proportional pressure regulator VPPM-6F-L-1-F-0L6H-V1N-S1 Part number: 542240

**FESTO** 

with electric setpoint specification and two-stage control circuit for stable, precise characteristic of regulation.





## **Data sheet**

| Feature                                 | Value  |
|---|--|
| Nominal diameter, pressurisation        | 6 mm   |
| Nominal diameter, exhaust               | 4.5 mm   |
| Type of actuation                       | electrical   |
| Sealing principle                       | soft   |
| Assembly position                       | Any  |
| Design structure                        | Pilot actuated diaphragm regulator   |
| Short circuit strength                  | for all electrical connections   |
| Safety instructions                     | VPPM safety position: If the power supply cable is interrupted, output pressure is maintained unregulated. |
| Polarity protected                      | for all electrical connections   |
| Type of reset                           | mechanical spring  |
| Type of piloting                        | Piloted  |
| Valve function                          | 3-way proportional-pressure regulator  |
| Type of display                         | LED  |
| Pressure regulation range               | 0.06 6 bar   |
| Inlet pressure 1                        | 0 8 bar  |
| Max. pressure hysteresis                | 0.03 bar   |
| Standard nominal flow rate              | 900 l/min  |
| Operating voltage range DC              | 21.6 26.4 V  |
| Max. current consumption                | 300 mA   |
| Duty cycle                              | 100 %  |
| Max. electrical power consumption       | 7 W  |
| Residual ripple                         | 10 %   |
| Switch output                           | NPN  |
| Signal range, analogue output           | 0 - 10 V   |
| Signal range, analogue input            | 0 - 10 V   |
| Operating medium                        | Compressed air in accordance with ISO8573-1:2010 [7:4:4]   |
|   | Inert gases  |
| Note on operating and pilot medium      | Lubricated operation not possible  |
| Authorisation                           | RCM Mark   |
|   | c UL us - Listed (OL)  |
| KC mark                                 | KC-EMV   |
| CE mark (see declaration of conformity) | to EU directive for EMC  |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress  |
| Medium temperature                      | 10 50 °C   |
| Protection class                        | IP65   |
| Ambient temperature                     | 0 60 °C  |
| Product weight                          | 400 g  |
| Linearity error, FS                     | 1 %  |
| Temperature coefficient                 | 0.04 %/K   |
| FS repetition accuracy                  | 0.5 %  |
| Electrical connection                   | 8-pin  |
|   | M12  |



| Feature                      | Value                   |
|------------------------------|-------------------------|
|                              | Plug                    |
| Mounting type                | with through hole       |
|                              | with accessories        |
|                              | Optional                |
| Pneumatic connection, port 1 | Sub-base Sub-base       |
| Pneumatic connection, port 2 | Sub-base                |
| Pneumatic connection, port 3 | Sub-base                |
| Materials note               | Conforms to RoHS        |
| Material housing             | Wrought Aluminium alloy |
|                              | Anodised                |