



solenoid valve

CPE14-M1CH-3OL-1/8

Part number: 550249

FESTO

Very compact assembly, with M8 plug connection.



Data sheet

| Feature | Value |
|---|--|
| Valve function | 3/2 open, monostable |
| Type of actuation | electrical |
| Width | 14 mm |
| Standard nominal flow rate | 900 l/min |
| Operating pressure | 2.5 ... 8 bar |
| Design structure | Piston slide |
| Type of reset | Air spring |
| Maritime classification | see certificate |
| Protection class | IP65 IP67 with plug socket to IEC 60529 |
| Nominal size | 6 mm |
| Sealing principle | soft |
| Assembly position | Any |
| Manual override | with accessories, detenting Pushing |
| Type of piloting | Piloted |
| Pilot air supply | Internal |
| Flow direction | non reversible |
| Valve position identification | Inscription label holder |
| Overlap | Positive overlap |
| Switching time off | 27 ms |
| Switching time on | 16 ms |
| Duty cycle | 100 % |
| Max. positive test pulse with logic 0 | 1,200 µs |
| Max. negative test pulse with logic 1 | 900 µs |
| Characteristic coil data | 24 V DC: 1.28 W |
| Permissible voltage fluctuation | -15 % / +10 % |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Vibration resistance | Transport application test at severity level 2 in accordance with FN 942017-4 and EN 60068-2-6 |
| Shock resistance | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Medium temperature | -5 ... 50 °C |
| Ambient temperature | -5 ... 50 °C |
| Max.tightening torque plug | 0.4 Nm |
| Product weight | 60 g |
| Electrical connection | 4-pin M8x1 |
| Mounting type | with through hole |

| Feature | Value |
|------------------------------|--------------------|
| Pilot exhaust port 82 | M3 |
| Pilot air port 12 | M3 |
| Pneumatic connection, port 1 | G1/8 |
| Pneumatic connection, port 2 | G1/8 |
| Pneumatic connection, port 3 | G1/8 |
| Materials note | Conforms to RoHS |
| Material seals | NBR |
| Material housing | Aluminium die cast |