
## sub-base VMPAL-AP-20-QS10-1 Part number: 560991





## **Data sheet**

| Feature                                 | Value                                                                       |
|-----------------------------------------|-----------------------------------------------------------------------------|
| Width                                   | 21.2 mm                                                                     |
| Length                                  | 107.3 mm                                                                    |
| Grid dimension                          | 21.2 mm                                                                     |
| Valve size                              | 20 mm                                                                       |
| Max. number of valve positions          | 1                                                                           |
| Flow direction                          | reversible                                                                  |
| Valve terminal structure                | Valve sizes can be mixed                                                    |
| Max. number of solenoid coils           | 1                                                                           |
| Operating pressure                      | -0.9 10 bar                                                                 |
| Pilot pressure                          | 3 8 bar                                                                     |
| Operating medium                        | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                    |
| Note on operating and pilot medium      | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 3 - High corrosion stress                                                   |
| Ambient temperature                     | -5 50 °C                                                                    |
| Product weight                          | 82.18 g                                                                     |
| Pneumatic connection, port 2            | For tubing outside diameter 10 mm                                           |
| Pneumatic connection, port 4            | for tubing, 10mm outside diameter                                           |
| Materials note                          | Conforms to RoHS                                                            |
| Material of connecting plate            | PA-reinforced                                                               |