

## solenoid valve VSVA-B-T22CV-AZD-D1-2AT1L Part number: 561345

For valve terminal VTSA.





**FESTO** 

## **Data sheet**

Feature	Value
Valve function	2x2/2 closed, monostable
Type of actuation	electrical
Width	42 mm
Standard nominal flow rate	1,400 l/min
Operating pressure	-0.9 10 bar
Design structure	Piston slide
Type of reset	Air spring
CE mark (see declaration of conformity)	to EU directive low-voltage devices
Protection class	IP65
	NEMA 4
Exhaust-air function	throttleable
	Via individual sub-base
Sealing principle	soft
Assembly position	Any
Manual override	detenting
	Pushing
	Covered
Type of piloting	Piloted
Pilot air supply	external
Flow direction	Any
Signal status display	LED
Pilot pressure	3 10 bar
Flow rate of valve	1,600 l/min
Flow rate of valve on individual sub-base	1,400 l/min
Optimised flow rate of valve pneumatically concatenated flow	1,500 l/min
Flow rate of pneumatically linked valve	1,400 l/min
Switching time off	46 ms
Switching time on	22 ms
Characteristic coil data	110/120 V AC: 50/60 Hz, power 1.0 VA
Surge strength	2.5 kV
Degree of contamination	3
Permissible voltage fluctuation	+/- 10 %
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Vibration resistance	Transport application test at severity level 2 in accordance with FN 942017-4 and EN 60068-2-6
Shock resistance	Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27
Corrosion resistance classification CRC	0 - No corrosion stress
Relative air humidity	0 - 90 %
Ambient temperature	-5 50 °C
Product weight	442 g
Electrical connection	Plug-in



Feature	Value	
	as per ISO 5599-2	
Mounting type	On sub-base	
Auxiliary pilot air port 12/14	Sub-base size 1 to ISO 5599-2	
Pilot exhaust port 82/84	Optional	
	Not ducted as per standard	
	Ducted	
Pneumatic connection, port 1	Sub-base size 1 to ISO 5599-2	
Pneumatic connection, port 2	Sub-base size 1 to ISO 5599-2	
Pneumatic connection, port 3	Sub-base size 1 to ISO 5599-2	
Pneumatic connection, port 4	Sub-base size 1 to ISO 5599-2	
Pneumatic connection, port 5	Sub-base size 1 to ISO 5599-2	
Materials note	Conforms to RoHS	
Material seals	FPM	
	HNBR	
	NBR	
Material housing	Aluminium die cast	
	PA	
Material screws	Galvanised steel	