



# radial gripper HGRT-40-A-G2

Part number: 563913

FESTO

With gripping force backup when closing...-G2.



## Data sheet

Feature	Value
Size	40
Max. replacement accuracy	$\leq 0.2$ mm
Max. angular gripper jaw backlash ax,ay	$\leq 0.1$ deg
Max. opening angle	180 deg
Rotationally symmetrical	$\leq 0.2$ mm
Repetition accuracy, gripper	$\leq 0.02$ mm
Number of gripper fingers	2
Assembly position	Any
Mode of operation	double-acting
Gripper function	radial
Design structure	guided motion sequence
Position detection	For proximity sensor For inductive sensors
Operating pressure	4 ... 8 bar
Max. operating frequency of gripper	$\leq 2$ Hz
Min. opening time at 6 bar	370 ms
Min. closing time at 6 bar	270 ms
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	1 - Low corrosion stress
Ambient temperature	5 ... 60 °C
Mass moment of inertia	15.26 kgcm <sup>2</sup>
Max. force on gripper jaw Fz static	400 N
Max. torque at gripper My static	17.5 Nm
Max. torque at gripper Mz static	1.6 Nm
Lubrication interval for guide components	10 Mio SP
Product weight	1,770 g
Mounting type	Internal thread and centring sleeve
Pneumatic connection	G1/8
Materials note	Free of copper and PTFE Conforms to RoHS
Material housing	Aluminium Smooth anodised
Material gripper jaws	Steel Hardened