

filter regulator

MS9-LFR-NG-D6-EUM-DI-AG-PSI-AS

Part number: 564124

FESTO

Maximum output pressure 7 bar, 40 µm filter, with pressure gauge, lockable regulator head, metal bowl guard, manual condensate drain, flow direction from left to right.



Data sheet

| Feature | Value |
|---|--|
| Size | 9 |
| Series | MS |
| Actuator lock | with accessories, lockable |
| Assembly position | Vertical +/- 5° |
| Grade of filtration | 40 µm |
| Condensate drain | manual rotary |
| Design structure | Directly actuated filter diaphragm regulator |
| Max. condensate volume | 220 ml |
| Controller function | Output pressure constant with initial pressure compensation with secondary exhaust with return flow |
| Pressure gauge | with pressure gauge |
| Operating pressure | 1 ... 20 bar |
| Pressure regulation range | 0.5 ... 7 bar |
| Max. pressure hysteresis | 0.4 bar |
| Operating medium | Compressed air to ISO 8573-1:2010 [-:4:] Inert gases |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Storage temperature | -10 ... 60 °C |
| Air purity class at output | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Medium temperature | -10 ... 60 °C |
| Ambient temperature | -10 ... 60 °C |
| Product weight | 2,400 g |
| Mounting type | Line installation with accessories Optional |
| Material of cover | PA-reinforced |
| Material of spin disc | POM |
| Material of filter holder | POM |
| Materials note | Conforms to RoHS |
| Material of connecting plate | Aluminium die cast |
| Material mounting bracket | Aluminium die cast |
| Material filter | PE |
| Material housing | Aluminium die cast |
| Material module connector | Aluminium die cast |
| Material membrane | NBR |
| Material bowl | Wrought Aluminium alloy |
| Material cup seal | NBR |
| Material screen | PA |
| Material separating plate | POM |
| Material valve stem | Wrought Aluminium alloy NBR POM |