

proportional pressure regulator VPPE-3-1-1/8-6-010-E1T

Part number: 567539

FESTO



Data sheet

| Feature | Value |
|---|--|
| Nominal diameter, pressurisation | 5 mm |
| Nominal diameter, exhaust | 2.5 mm |
| Type of actuation | electrical |
| Sealing principle | soft |
| Assembly position | Any Preferably upright |
| Design structure | Pilot actuated diaphragm regulator |
| Short circuit strength | for all electrical connections |
| Safety instructions | VPPE safety position: If the power supply cable is interrupted, output pressure is maintained unregulated. |
| Polarity protected | for all electrical connections |
| Type of reset | mechanical spring |
| Type of piloting | Piloted |
| Valve function | 3-way proportional-pressure regulator |
| Type of display | LED display 3-digit |
| Pressure regulation range MPa | 0.006 ... 0.6 MPa |
| Pressure regulation range | 0.06 ... 6 bar |
| Inlet pressure 1 | 6 ... 8 bar |
| Supply pressure 1 MPa | 0.6 ... 0.8 MPa |
| Max. pressure hysteresis (MPa) | 0.003 MPa |
| Max. pressure hysteresis | 0.03 bar |
| Standard nominal flow rate | 800 l/min |
| Operating voltage range DC | 21.6 ... 26.4 V |
| Max. current consumption | 160 mA |
| Duty cycle | 100 % |
| Max. electrical power consumption | 4.2 W |
| Residual ripple | 10 % |
| Switch output | PNP |
| Signal range, analogue output | 0 - 10 V |
| Signal range, analogue input | 0 - 10 V |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] Inert gases |
| Note on operating and pilot medium | Lubricated operation not possible |
| Authorisation | RCM Mark c UL us - Listed (OL) |
| KC mark | KC-EMV |
| CE mark (see declaration of conformity) | to EU directive for EMC |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Medium temperature | 10 ... 50 °C |
| Protection class | IP65 |
| Ambient temperature | 0 ... 60 °C |
| Product weight | 390 g |
| Linearity error in ± %FS | 1 %FS |
| Temperature coefficient | 0.04 %/K |
| Repetition accuracy in ± %FS | 0.5 %FS |

| Feature | Value |
|------------------------------|---|
| Electrical connection | 5-pin M12 Plug |
| Mounting type | with through hole |
| Pneumatic connection, port 1 | G1/8 |
| Pneumatic connection, port 2 | G1/8 |
| Pneumatic connection, port 3 | G1/8 |
| Materials note | Free of copper and PTFE Conforms to RoHS |
| Material housing | Wrought Aluminium alloy Anodised |