


compact cylinder ADN-40-20-I-PPS-A

Part number: 572666

★ Core product range

with self-adjusting pneumatic end position cushioning

FESTO



Data sheet

| Feature | Value |
|--|--|
| Stroke | 20 mm |
| Piston diameter | 40 mm |
| Piston rod thread | M8 |
| Cushioning | PPS: Self-adjusting pneumatic end-position cushioning |
| Assembly position | Any |
| Conforms to standard | ISO 21287 |
| Piston-rod end | Female thread |
| Position detection | For proximity sensor |
| Variants | Single-ended piston rod |
| Operating pressure | 1 ... 10 bar |
| Mode of operation | double-acting |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress |
| Ambient temperature | -20 ... 80 °C |
| Impact energy in end positions | 1.7 J |
| Cushioning length | 5 mm |
| Theoretical force at 6 bar, return stroke | 686 N |
| Theoretical force at 6 bar, advance stroke | 754 N |
| Moving mass with 0 mm stroke | 80 g |
| Additional weight per 10 mm stroke | 37 g |
| Basic weight for 0 mm stroke | 346 g |
| Additional mass factor per 10 mm of stroke | 9 g |
| Mounting type | with through hole with internal (female) thread with accessories Optional |
| Pneumatic connection | G1/8 |
| Materials note | Conforms to RoHS |
| Material cover | Aluminium Anodised |
| Material seals | TPE-U(PUR) |
| Material piston rod | High alloy steel |
| Material cylinder barrel | Wrought Aluminium alloy Smooth anodised |