



# solenoid valve

## VUVS-L30-M32C-AZD-G38-F8-1B2

Part number: 575573

FESTO



### Data sheet

| Feature                                 | Value  |
|---|--|
| Valve function                          | 3/2 closed, monostable   |
| Type of actuation                       | electrical   |
| Valve size                              | 31 mm  |
| Standard nominal flow rate              | 2,300 l/min  |
| Operating pressure                      | -0.9 ... 10 bar  |
| Design structure                        | Piston slide   |
| Type of reset                           | Air spring   |
| Authorisation                           | c UL us - Recognized (OL)  |
| Maritime classification                 | see certificate  |
| Certificate issuing department          | DNVGL-TAA000011J   |
| Protection class                        | IP65<br>with plug socket<br>to IEC 60529   |
| Nominal size                            | 9.4 mm   |
| Exhaust-air function                    | throttleable   |
| Sealing principle                       | soft   |
| Assembly position                       | Any  |
| Manual override                         | detenting<br>Pushing   |
| Type of piloting                        | Piloted  |
| Pilot air supply                        | external   |
| Flow direction                          | reversible   |
| Overlap                                 | Positive overlap   |
| Pilot pressure                          | 2.5 ... 10 bar   |
| b value                                 | 0.3  |
| C value                                 | 9.8 l/sbar   |
| Switching time off                      | 36 ms  |
| Switching time on                       | 19 ms  |
| Duty cycle                              | 100 %  |
| Max. positive test pulse with logic 0   | 2,000 µs   |
| Max. negative test pulse with logic 1   | 3,600 µs   |
| Characteristic coil data                | 24 V DC: 3.3 W   |
| Permissible voltage fluctuation         | +/- 10 %   |
| Operating medium                        | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                                       |
| Note on operating and pilot medium      | Lubricated operation possible (subsequently required for further operation)                    |
| Vibration resistance                    | Transport application test at severity level 2 in accordance with FN 942017-4 and EN 60068-2-6 |
| Shock resistance                        | Shock test with severity level 2 in accordance with FN 942017-5 and EN 60068-2-27              |
| Corrosion resistance classification CRC | 2 - Moderate corrosion stress  |
| Medium temperature                      | -10 ... 60 °C  |
| Pilot medium                            | Compressed air in accordance with ISO8573-1:2010 [7:4:4]                                       |
| Ambient temperature                     | -10 ... 60 °C  |
| Product weight                          | 405 g  |
| Electrical connection                   | Plug pattern type B to EN 175301-803   |

| Feature                       | Value   |
|-------------------------------|---|
| Mounting type                 | on manifold rail<br>with through hole<br>Optional |
| Scavenging orifice connection | Non-ducted  |
| Pilot exhaust port 82         | M5  |
| Pilot air port 12             | G1/8  |
| Pneumatic connection, port 1  | G3/8  |
| Pneumatic connection, port 2  | G3/8  |
| Pneumatic connection, port 3  | G3/8  |
| Materials note                | Conforms to RoHS                                  |
| Material seals                | HNBR<br>NBR                                       |
| Material housing              | Aluminium die cast<br>Painted                     |
| Material Piston slide         | Wrought Aluminium alloy                           |
| Material screws               | Steel, nickel-plated                              |