

pressure sensor SPAW-P10R-G12M-2PV-M12

Part number: 8022807

FESTO

For measuring media pressures, pressure measuring range between 0 and +10 bar, pneumatic connection male thread G1/2.



Data sheet

| Feature | Value |
|---|---|
| Authorisation | RCM Mark c UL us - Listed (OL) |
| CE mark (see declaration of conformity) | to EU directive for EMC |
| Materials note | Contains PWIS substances Conforms to RoHS |
| Measured variable | Relative pressure |
| Measurement method | Thin metal film pressure sensor |
| Pressure measuring range, initial value | 0 bar |
| Pressure measuring range, final value | 10 bar |
| Overload range | 20 bar |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [-:::] Fluid media Gaseous media |
| Medium temperature | -20 ... 85 °C |
| Ambient temperature | 0 ... 80 °C |
| Accuracy, FS | 1 %FS |
| Repetition accuracy in ± %FS | 0.15 %FS |
| Switch output | 2xPNP |
| Switching function | Freely programmable |
| Switching element function | Switchable |
| Max. output current | 250 mA |
| Analogue output | 0 - 10 V |
| Rise time | 3 ms |
| Short circuit strength | Yes |
| Operating voltage range DC | 15 ... 35 V |
| Polarity protected | for operating voltage |
| Electrical connection | 5-pin M12x1 Plug to EN 60947-5-2 Round design |
| Mounting type | with external (male) thread |
| Assembly position | Any |
| Pneumatic connection | Male thread G1/2 |
| Product weight | 230 g |
| Material housing | ABS High alloy steel, non-corrosive |
| Materials in contact with media | High alloy steel, non-corrosive |
| Material sealing ring | NBR |
| Type of display | 4-place alphanumeric LED display |
| Unit(s) that can be displayed | MPa bar |

| Feature | Value |
|---|----------------------------------|
| | kPa kg/cm ² psi |
| Operating status display | Red LED |
| Setting options | Via display and buttons |
| Protection against manipulation | PIN-Code |
| Threshold value setting range | 0.5 ... 100 % |
| Hysteresis setting range | 0.5 ... 99.5 % |
| Protection class | IP65 IP67 |
| Corrosion resistance classification CRC | 4 - Very high corrosion stress |