


# Line choke CAMF-C6-FD-C6-3A

Part number: 8088930

☆ Core product range

FESTO



## Data sheet

Feature	Value
Short circuit strength	No
Acceptable current load at 40°C	6 A
Operating voltage range AC	0 ... 400 V
Nominal operating voltage, AC	400 V
Nominal inductance	5.7 mH
Nominal inductance tolerance	10 %
Line frequency	50 ... 60 Hz
Insulation voltage	2,500 V
Authorisation	ENEC c UL - Recognized (OL)
CE mark (see declaration of conformity)	in accordance with EU RoHS directive
Storage temperature	-10 ... 40 °C
Protection class	IP00
Ambient temperature	-10 ... 40 °C
Product weight	2,000 g
Mounting type	Mounting plate, bolted
Materials note	Contains PWIS substances Conforms to RoHS
Assembly position	Horizontal
Electrical connection 1, function	Power supply
Electrical connection 1, connection type	Terminal strip
Electrical connection 1, connection technology	Screwed terminal
Electrical connection 1, number of pins/wires	2
Electrical connection 1, occupied pins/wires	2
Electrical connection 1, conductor cross section	4 mm <sup>2</sup>
Electrical connection 2, function	Power supply
Electrical connection 2, connection type	Terminal strip
Electrical connection 2, connection technology	Screwed terminal
Electrical connection 2, number of pins/wires	2
Electrical connection 2, occupied pins/wires	2
Electrical connection 2, conductor cross section	4 mm <sup>2</sup>